



BILLET SUPERLITE SL6R RADIAL MOUNT CALIPERS

www.wilwood.com

SL6R CALIPER, MOUNTING DIMENSIONS:

TOP OF FRICTION MATERIAL AND DISC O.D. TO BE FLUSH

9.44 (239,8) DISC ROTATION

1.62 (41,1) PISTON

1.12 (28,4) PISTON(S)

1.62 (41,1) MOUNT HEIGHT

6 PISTON

5.98 (152,0) MOUNT CENTER

"E" OUTSIDE RADIUS

"D1"

DISC/WHEEL CENTERLINE

DISC WIDTH

2.35 (59,7)

2.35 (59,7) SEE NOTE 1

"B" MOUNT OFFSET

DISC WIDTH	"B" MOUNT OFFSET
1.38 (35,1)	1.80 (45,7)
1.25 (31,8)	1.80 (45,7)
1.10 (27,9)	1.70 (43,2)
1.00 (25,4)	1.70 (43,2)
.81 (20,6)	1.58 (40,1)

DISC DIAMETER	"E" OUTSIDE RADIUS
11.75 (298,5)	6.65 (168,9)
12.19 (309,6)	6.81 (173,0)
12.72 (323,1)	7.00 (177,8)
12.88 (327,2)	7.07 (179,6)
13.00 (330,2)	7.13 (181,1)

DIMENSION "D1" = (DISC DIAMETER/2) - 1.62 (41,1)

NOTE 1: DIMENSION FOR WIDE 5 HUB APPLICATION IS 2.13 (54,1)

NOTE 2: RIGHT HAND REAR MOUNT CALIPER SHOWN.

INLET FITTING: 1/8-27 NPT

RADIAL MOUNT BRACKETS ARE AVAILABLE

RADIAL CALIPER TO LUG MOUNT ADAPTER BRACKET, PART NUMBER 250-6309:

5.98 (152,0)

1.14 (28,9)

3.50 (88,9) MOUNT CENTER

.45 (11,4) MOUNT HOLE

1.64 (41,7)

.26 (6,6)

NOTE: BRACKET KIT INCLUDES STUDS, LOCKNUTS, WASHERS AND ALIGNMENT SHIMS

RADIAL CALIPER TO LUG MOUNT ADAPTER BRACKET, PART NUMBER 250-6308:

5.98 (152,0)

1.57 (39,9)

5.25 (133,4) MOUNT CENTER

.45 (11,4) MOUNT HOLE

2.09 (53,1)

.30 (7,6)

NOTE: BRACKET KIT INCLUDES STUDS, LOCKNUTS, WASHERS AND ALIGNMENT SHIMS

CALIPERS

WARNING: The user or installer of any product from this catalog must determine its suitability for their intended purpose or application