## BILLET SL6 AND SL6/ST WITH NARROWED OUTBOARD BODY:

Calipers in this group feature a reduced width outboard body to provide additional clearance between the caliper face and the wheel or hub. These calipers were originally built for use with wide 5 hubs, but have found their way to other close fit wheel and hub applications. The caliper bridge radius will clear rotors from 11.75" to 13.00" in overall diameter. Each caliper in this group uses 7420 type 20mm thick pads. Specific mounting and body width dimensions can be found in the chart on page 26, with dimensional variations outlined in note 1.



Black

NARROWED SL6 WITH STAINLESS STEEL PISTONS CALIPER ORDERING INFORMATION: <sup>(1)</sup>							
		FRONT MOUNT PART NO.		REAR MOUNT PART NO.			
BORE SIZE	DISC WIDTH	<u>RH</u>	<u>LH</u>	<u>RH</u>	<u>LH</u>		
1.62 / 1.12 / 1.12"	1.25" 31,8 mm	120-6584-FS	120-6585-FS	120-6584-RS	120-6585-RS		
41.1 / 28.4 / 28.4 mm							

# SL6 WITH THERMLOCK<sup>®</sup> PISTONS CALIPER ORDERING INFORMATION:<sup>(1)</sup>

		FRONT MOUNT PART NO.		<b>REAR MOUNT PART NO.</b>	
BORE SIZE	DISC WIDTH	<u>RH</u>	LH	<u>RH</u>	<u>LH</u>
1.62 / 1.12 / 1.12"	1.25" 31,8 mm	120-6387-FS	120-6388-FS	120-6387-RS	120-6388-RS
41,1 / 28,4 / 28,4 mm					

### NARROWED BODY SL6 FOR 16MM PADS:



Calipers in this group have the narrowest profile in the entire SL6 category. They are designed for use with 16mm thick 7416 type pads over 1.10" width rotors between 11.75" and 13.00" in diameter. These calipers are primarily used in OE performance "Big Brake" conversion kits and other custom applications with extreme space limitations. Fully polished calipers are also available for custom show car applications. Specific mounting and body width dimensions can be found in the chart on page 26, with dimensional variations outlined in note 2.

### NARROWED BODY SL6 FOR 16MM PADS - BLACK CALIPER ORDERING INFORMATION:<sup>(1)</sup>

		FRONT MOUNT PART NO.		<b>REAR MOUNT PART NO.</b>	
BORE SIZE	DISC WIDTH	<u>RH</u>	<u>LH</u>	<u>RH</u>	<u>LH</u>
1.62 / 1.12 / 1.12"	1.10" 27,9 mm	120-7228-FS <sup>(2)</sup>	120-7229-FS <sup>(2)</sup>	120-7228-RS <sup>(2)</sup>	120-7229-RS <sup>(2)</sup>
41,1 / 28,4 / 28,4 mm					

#### NARROWED BODY SL6 FOR 16MM PADS - POLISHED CALIPER ORDERING INFORMATION:<sup>(1)</sup>

		REAR MOUNT PART NUMBER		
BORE SIZE	DISC WIDTH	<u>RH</u>	<u>LH</u>	
1.62 / 1.12 / 1.12"	1.10" 27,9 mm	120-7259-RSP	120-7260-RSP	
41,1 / 28,4 / 28,4 mm				

NOTES: (1) REFERENCE FRONT OF MANUAL FOR GENERAL ORDERING INFORMATION (2) AVAILABLE RED, ADD "R" TO END OF PART NUMBER WHEN ORDERING FS = FRONT SIDE MOUNT, RS = REAR SIDE MOUNT, SI = SIDE INLET

Brakes are critical safety components, see warnings and disclaimer on page 131

CALIPERS