

P6R RADIAL MOUNT CALIPER

Caliper Highlights:

Wilwood's six piston P6R caliper leads the pack in Short Track and Road Course braking technology. Thermlock® T2 insulated short track pistons come standard in the P6R and are positioned employing our proven exclusive stagger pattern resulting in unmatched caliper rigidity and balanced pad load characteristics. Holding a large 13.2 cubic inch pad, it is designed with heat management technology derived from years of short track experience combined with the latest in solid modeling and stress simulation programs. Brake pad distortion and taper is virtually eliminated. Pedal feel is responsive, predictable and consistent.




Weighing just 7.2 pounds, this ultra-stiff radial mount caliper comes with **Thermlock**[®] **T2** pistons and is fully heat shielded for maximum seal life and brake fluid protection. Additional features include dual bridge bolts, heavy duty pad load plates and protected two-piece bleed screws and crossover tube. We also offer a lightweight mounting bracket from 7.80" (198,1) radial to 5.25" (133,4) **GT** lug mount pattern. Self bleed lines are available for the **P6R**.

THERMLOCK T2 SHORT TRACK PISTON:

Wilwood's **Thermlock**® **T2** pistons incorporate a stainless steel shield and coated aluminum shell configuration to provide a highly efficient thermal barrier between the brake pads and the caliper body, seals, and fluid. Lower operating temperatures eliminate seal crystallization and localized fluid boiling while providing longer caliper service life through decreased distortion in the caliper body and piston bores. **Thermlock® T2** pistons are standard equipment in all P6R calipers.

1.62" (41,1 mm) Diameter - Order P/N: 200-7398 1.25" (31,8 mm) Diameter - Order P/N: 200-7402



CALIPER ORDERING INFORMATION:(1)

 BORE SIZE
 DISC WIDTH
 RH
 LH
 RH
 LH

 1.62 / 1.25 / 1.25"
 1.38" 35,1 mm
 120-7604-FS
 120-7605-FS
 120-7604-RS
 120-7605-RS

 41,1 / 31,8 / 31,8 mm
 120-7605-FS
 120-7605-FS
 120-7605-RS

CALIPER MOUNTING BRACKET KIT 7.80" (198,1) RADIAL TO 5.25" (133,4) GT LUG - P/N: 250-7426

NOTES: (1) REFERENCE FRONT OF MANUAL FOR GENERAL ORDERING INFORMATION (FS = FRONT SIDE MOUNT, RS = REAR SIDE MOUNT)