

BANJO BOLTS & CONNECTORS

Most banjo bolts are also available in aluminum and stainless. To order **aluminum** - change the first digit of part number from a "4" to a "9" EXAMPLE: 494303 changes to 994303. To order **stainless** - change the first digit of part number from a "4" to a "5" EXAMPLE: 494303 changes to 594303.
 *Harley Series - For 7/16"-24 single bolt, use Part No. 494724.

Only available in stainless



3-WAY THREAD ON BRANCH

SIZE	DESCRIPTION	PART NO.
3	3/8"-24 JIC BRANCH	451073

Only available in stainless



DOUBLE TAKE OFF 90° BANJO

SIZE	DESCRIPTION	PART NO.
3	M10, 3/8", SERIES 2	441703

Only available in stainless



3-WAY MALE W/BACKET

SIZE	DESCRIPTION	PART NO.
3	3-WAY CONNECTOR	451103



3-WAY HOSE W/BACKET

SIZE	DESCRIPTION	PART NO.
3	3-WAY W/ BACKET	451113



DOUBLE TAKE OFF BANJO

SERIES	DESCRIPTION	PART NO.
1	-3 HOSE EXTENDED	445703
2	-3 HOSE	441603
2	-3 MALE	441513

Only available in stainless



3-WAY HOSE BANJO

SIZE	DESCRIPTION	PART NO.
3	3/8", M10	441123

USES SERIES 2 BOLT

OUR TEFLON® BRAID SEPARATING TOOL MAKES ASSEMBLY EASY

Using XRP's Separating Tool is the quickest way to flare stainless braid away from -3 and -4 Teflon hose for easy insertion of the olive during assembly. **PART NO. 821060**



STEP ONE Insert hose on arbor.



STEP TWO Flare braid using a twisting motion.



STEP THREE Insert olive on tube and under braid.



STEP FOUR Seat olive with a push.

SEE PAGE 57 FOR COMPLETE ASSEMBLY INSTRUCTIONS.