

SILICONE HOSE

Silicone hose operating pressure varies from 50 PSI to 110 PSI depending on size. Fluid and vacuum hoses have a maximum operating temperature of 350° F. Turbo hoses have a maximum operating temperature of 500° F. **DO NOT USE WITH GASOLINE.**

COOLANT HOSE



PART NO.	I.D.
370100	1"
370125	1-1/4"
370150	1-1/2"
370175	1-3/4"
370200	2"
370225	2-1/4"
370250	2-1/2"
370275	2-3/4"
370300	3"

All sizes available in 3' lengths **ONLY**.
Custom lengths to 12'.

VACUUM HOSE



PART NO.	I.D.
350012	1/8"
350018	3/16"
350025	1/4"
350031	5/16"
350038	3/8"

All sizes available in 25' or 50'
lengths **ONLY**.


HEATER HOSE



PART NO.	I.D.
380025	1/4"
380031	5/16"
380038	3/8"
380050	1/2"
380062	5/8"
380075	3/4"
380100	1"

All sizes available in 25' or 50'
lengths **ONLY**.

PREFORMED HOSE



	45°	90°	I.D.	RADIUS
-	390100	1"	1.5"	
-	390125	1-1/4"	1.75"	
-	390150	1-1/2"	2"	
345175	390175	1-3/4"	1.75"	
-	390200	2"	4"	
-	390225	2-1/4"	4"	
-	390250	2-1/2"	3"	
-	390275	2-3/4"	3.5"	


Other sizes available on request.

TURBO HOSE

3-PLY



4-PLY



3-PLY	4-PLY	I.D.
362125	364125	1-1/4"
362150	364150	1-1/2"
362175	364175	1-3/4"
362200	364200	2"
362250	364250	2-1/2"
362275	364275	2-3/4"
362300	364300	3"
362312	364312	3-1/8"
362350	364350	3-1/2"

All sizes available in 3' lengths **ONLY**.
62 Series is 3-ply glass fiber reinforced.
64 Series is 4-ply glass fiber reinforced.

LINER* HOSE CLAMPS FOR SILICONE HOSE



PART NO.	QTY.	SIZE
819406	4	9/16 - 13/16
819408	4	11/16 - 15/16
819410	4	13/16 - 1-1/16
819412	4	15/16 - 1-1/4
819420	4	1 - 1-3/4
819428	2	1-5/16 - 2-1/4
819436	2	1-13/16 - 2-3/4
819440	2	2-1/16 - 3
819444	2	2-5/16 - 3-1/4
819448	2	2-9/16 - 3-1/2
819460	2	2-5/16 - 4-1/4

*Fully lined to prevent extrusion of hose through band.